

## FUSION GLASS infrarood panelen



Fusion Glass F-6 Spiegel



ophanging Fusion Glass



Fusion Glass F-8 zwart

Infrarood panelen Fusion Glass	Gewicht (kg)	Vermogen (watt)	Afmetingen (cm)	Oppervlakte temperatuur (°C)	Maximale afstand/hoogte (m)
F-4 Spiegel	6	400	60 x 60 x 2,5	85 - 110	2,50 - 2,70
F-6 Spiegel	9	600	90 x 60 x 2,5	85 - 110	2,50 - 2,70
F-6 Zwart	9	600	90 x 60 x 2,5	85 - 110	2,50 - 2,70
F-8 Zwart	14	800	120 x 60 x 2,5	85 - 110	2,50 - 2,70
F-6 Wit	9	600	90 x 60 x 2,5	85 - 110	2,50 - 2,70
F-8 Wit	14	800	120 x 60 x 2,5	85 - 110	2,50 - 2,70

### Eigenschappen Fusion Glass infrarood panelen:

- Oppervlaktetemperaturen tot plm. 110 °C;
- Hoog rendement (93%);
- IP-44 classificering (spatwaterbestendig);
- Opwarmtijd (tot maximale temperatuur): plm. 15 – 20 minuten;
- TÜV gekeurd en CE gecertificeerd;
- Voldoet aan alle Europese-, USA- en Canadese security standards;
- 4 Jaar garantie;

